



pureliQ:	K			KD			R			RD			A			AD		
Hauswassereingangsfiter mit sanft organischem Design	✓			✓			✓			✓			✓			✓		
Nennweite [DN]	20	25	32	20	25	32	20	25	32	20	25	32	20	25	32	20	25	32
Nenndurchfluss $\Delta p = 0,2 \text{ bar}$ [m³/h]	2,8	3,7	4,0	—			3,2	4,2	5,0	—			3,2	4,2	5,0	—		
$\Delta p = 0,5 \text{ bar}$ [m³/h]	4,5	6,0	6,3	—			5,1	6,7	8,0	—			5,1	6,7	8,0	—		
n. DIN EN 1567 [m³/h]	—			2,3	3,6	5,8	—			2,3	3,6	5,8	—			2,3	3,6	5,8
Filterfeinheit (obere/untere Durchlassweite) [µm]	100 (120/80)			100 (120/80)			100 (120/80)			100 (120/80)			100 (120/80)			100 (120/80)		
Nenndruck	PN 16			PN 16			PN 16			PN 16			PN 16			PN 16		
Austauschbares Filterelement	✓			✓			—			—			—			—		
Drehbarer Klick-Anschlussflansch	✓			✓			✓			✓			✓			✓		
UV-Schutz mit Sichtfenster	✓			✓			✓			✓			✓			✓		
Druckminderer mit ergonomischem Handrad (Werkseinstellung 4 bar)	—			✓			—			✓			—			✓		
Schlauchadapter	—			—			✓			✓			—			—		
Vortex-Rückspültechnologie	—			—			✓			✓			✓			✓		
Flexibler Kanalanschluss	—			—			✓			✓			✓			✓		
Automatische Rückspülung mit einstellbaren Intervallen	—			—			—			—			✓			✓		